

MULTIFUNCTION GANGWAYS 3626

extension 1450 mm to 2590 mm, H box: 230 mm



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	D (mm/ inch)	E (mm/ inch)	G (mm/ inch)	L (mm/ inch)	H (mm/ inch)	α	β	n° steps
3626/15	1450 57"	1950 76" ³ / ₄	230 9"	680 26" ³ / ₄	1120 44"	470 18" ¹ / ₂	590 23" ¹ / ₅	230 9"	35°	70°	6
3626S20	1825 71" ⁹ / ₁₀	2400 94" ¹ / ₂	275 10" ⁴ / ₅	830 32" ³ / ₅	1365 53" ³ / ₄	470 18" ¹ / ₂	660 26"	230 9"	35°	70°	7
3626/20	1850 72" ⁴ / ₅	2340 92" ¹ / ₁₀	340 13" ² / ₅	830 32" ³ / ₅	1365 53" ³ / ₄	470 18" ¹ / ₂	590 23" ¹ / ₅	230 9"	35°	70°	7
3626/21	2100 82" ⁷ / ₁₀	2590 102"	340 13" ² / ₅	975 38" ² / ₅	1600 63"	470 18" ¹ / ₂	590 23" ¹ / ₅	230 9"	35°	70°	8
3626/31	2590 102"	3125 123"	340 13" ² / ₅	1260 49" ³ / ₅	2070 81" ¹ / ₂	470 18" ¹ / ₂	590 23" ¹ / ₅	230 9"	35°	70°	10

Optional box: weathertight, watertight and certificated watertight.

Models 3626 are available upon request with optional tilting angles +50° (α) and -50° (β).

This gangway allows the boarding of 120 Kg / 264,5 lbs maximum (one person at a time).

NEVER USE THE GANGWAY AS SPRINGBOARD. DIVING COULD CAUSE STRONG STRAINS THAT MIGHT DAMAGE THE GANGWAY AND ITS FASTENING ELEMENTS.

— LEAD TIME TO BE CONFIRMED

