

ROTATING BOX GANGWAY 1212/13

extension 3790 mm to 7295 mm, H box: 290 mm to 350 mm



model	N. elements	A (mm/ inch)	B (mm/ inch)	B/A (mm/ inch)	B/B (mm/ inch)	C (mm/ inch)	L (mm/ inch)	H (mm/ inch)	α	β	$\alpha 1$	$\beta 1$	lifting (kg/lbs)	weight (kg/lbs)
1212/38	2	3790 149"	--	3050 120"	3400 134"	1000 39"	600 23"	290 11"	60°	10°	10°	110°	400/880	860/1895
1212/42	2	4170 164"	--	--	3800 150"	1000 39"	600 23"	290 11"	60°	10°	10°	110°	400/880	920/2030
1213/39	3	3880 153"	3100 122"	--	--	640 25"	600 24"	290 11"	54°	15°	60°	60°	350/770	910/2000
1213/55	3	5490 216"	5000 197"	--	--	1530 60"	620 25"	350 15"	45°	15°	60°	60°	350/770	1680/3700
1213/73	3	7295 287"	5560 219"	--	--	1650 65"	1000 39"	350 15"	15°	15°	60°	60°	--	1830/4030

Optional box: weathertight, watertight and certificated watertight.

Gangway models with H.BOX 290mm can be made with stainless steel box H250mm (OPTIONAL).

This gangway allows the boarding of 150 Kg / 330 lbs maximum (one person at a time).

IDEAL FOR JET SKI AND TENDER LIFTING.

Option 1: this model is prearranged for hydraulic opening system with devices 2645, 2648 and 2649.

Option 2: electronically controlled steps for a better approach to boat deck.

NEVER USE THE GANGWAY AS SPRINGBOARD. DIVING COULD CAUSE STRONG STRAINS THAT MIGHT DAMAGE THE GANGWAY AND ITS FASTENING ELEMENTS.

LEAD TIME TO BE CONFIRMED

