

MANUAL STEPLADDER INTEGRATED WITH MOBILE PLATFORM **3239** extension 970 mm to 1660 mm



model	H (mm/inch)	A (mm/inch)	B (mm/inch)	L (mm/inch)	S1 (mm/inch)	S2 (mm/inch)	α	n° steps
3239/03	970 38 ¹¹ / ₁₆	600 23 ³ / ₁₆	735 28 ⁹ / ₁₆	736 29"	200 7 ⁹ / ₁₆	330 13"	15°	3
3239/04	1200 47 ¹ / ₄	600 23 ³ / ₁₆	975 38 ² / ₅	736 29"	200 7 ⁹ / ₁₆	390 15 ¹ / ₂	15°	4
3239/05	1430 56 ³ / ₁₀	600 23 ³ / ₁₆	1215 47 ⁴ / ₅	736 29"	200 7 ⁹ / ₁₆	450 17 ⁷ / ₁₀	15°	5
3239/06	1660 65 ¹ / ₂	600 23 ³ / ₁₆	1455 57 ³ / ₁₀	736 29"	200 7 ⁹ / ₁₆	510 20"	15°	6

Transom ladder with 3/6 steps connected to the platform.

The ladder is moved by the platform to a position that allows the access from the platform to the deck. 3/6 steps on the reclining section and 1 fixed step on the fastening bracket.

POSSIBLE CUSTOMIZATION OF DIMENSIONS

PATENTED SYSTEM

