

Pantograph door 2332.42/43



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	L (mm/ inch)	La (mm/ inch)	H (mm/ inch)	He (mm/ inch)	Sm (mm/ inch)	S (mm/ inch)	St (mm/ inch)	opening	weather proof ISO 12216:2023
2332/42	515 20 ³ / ₁₀	1670 65 ³ / ₄	300 11 ⁴ / ₅	660 25 ⁹ / ₁₀	695 27 ² / ₅	1750 69"	1805 71 ¹ / ₁₀	50 2"	105 4 ¹ / ₅	225 8 ⁴ / ₅	Sx←Dx	CAT 2
2332/43	515 20 ³ / ₁₀	1670 65 ³ / ₄	300 11 ⁴ / ₅	660 25 ⁹ / ₁₀	695 27 ² / ₅	1750 69"	1805 71 ¹ / ₁₀	50 2"	105 4 ¹ / ₅	225 8 ⁴ / ₅	Sx→Dx	CAT 2

Semiautomatic pantograph door (wing manual opening and automatic locking systems). Closing takes place thanks to four locking pins activated by electric actuators. Shaped wing made of fiberglass.

CERTIFIABLE BY RINA / BUREAU VERITAS / ABS / LLOYDS, please get in touch with our technical department to verify possible certifications.

The doors are subject to quality control tests to comply ISO 12216.2023 standards

NOTE: Sx→Dx, Sx←Dx

The sliding doors opening direction is always considered from the outside of the boat.

