

Pantograph door 2332.63



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	L (mm/ inch)	La (mm/ inch)	Lb (mm/ inch)	H (mm/ inch)	He (mm/ inch)	Sm (mm/ inch)	S (mm/ inch)	St (mm/ inch)	opening	weather proof ISO 12216:2023
2332/63	545 21 ¹ / ₂ "	1760 69 ³ / ₁₀ "	710 28"	730 28 ⁷ / ₁₀ "	825 32 ¹ / ₂ "	790 31 ¹ / ₁₀ "	1810 71 ³ / ₁₀ "	1930 79 ⁹ / ₁₀ "	50 2"	110 4 ³ / ₁₀ "	480 18 ⁹ / ₁₀ "	Sx←Dx	CAT 2

Semiautomatic pantograph door (wing manual opening and automatic locking systems).
Closing takes place thanks to four locking pins activated by electric actuators.
Shaped wing made of fiberglass.

CERTIFIABLE BY RINA / BUREAU VERITAS / ABS / LLOYDS, please get in touch with our technical department to verify possible certifications.
The doors are subject to quality control tests to comply ISO 12216.2023 standards
NOTE: Sx→Dx, Sx←Dx
The sliding doors opening direction is always considered from the outside of the boat.

