

# Hatches 2391.16



| model   | A (mm/inch)                           | B (mm/inch)                          | C (mm/inch)                            | R (mm/inch)                              | L (mm/inch)                           | H (mm/inch)                             | S (mm/inch)                          | $\alpha$ | weather proof<br>ISO 12216:2004 |
|---------|---------------------------------------|--------------------------------------|--|--|---------------------------------------|---|--------------------------------------|----------|---------------------------------|
| 2391/16 | 670<br>26 <sup>3</sup> / <sub>8</sub> | 70<br>27 <sup>4</sup> / <sub>8</sub> | 655<br>25 <sup>7</sup> / <sub>16</sub> | 9650<br>379 <sup>9</sup> / <sub>16</sub> | 900<br>35 <sup>2</sup> / <sub>8</sub> | 3195<br>125 <sup>4</sup> / <sub>8</sub> | 190<br>7 <sup>1</sup> / <sub>2</sub> | 37°      | CAT 2                           |

Upward-opening door with AUTOMATIC movement managed by a couple of hydraulic cylinders and pantograph lever mechanism.  
Tight automatic closing by means of six locking pins activated by ELECTRIC actuators.

This door can be certified in compliance with RINA/BUREAU VERITAS/LLOYDS requirements, upon request.  
ATTENTION! In case of certification request, dimensions and technical specifications may undergo significant variations.  
Please get in touch with our technical department to verify possible certifications.  
The doors are subject to quality control tests to comply ISO 12216.2004 standards.

