

# Companionway 2534.28



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	D (mm/ inch)	E (mm/ inch)	L (mm/ inch)	Le (mm/ inch)	H (mm/ inch)	He (mm/ inch)	S (mm/ inch)	$\alpha$	$\beta$	glass (mm/inch)	opening	weather proof ISO 12216:2004
2534/28	700 27 <sup>13</sup> / <sub>16</sub>	1460 57 <sup>13</sup> / <sub>16</sub>	850 33 <sup>11</sup> / <sub>16</sub>	415 16 <sup>3</sup> / <sub>16</sub>	725 28 <sup>11</sup> / <sub>16</sub>	1625 64"	1735 68 <sup>11</sup> / <sub>16</sub>	475 18 <sup>7</sup> / <sub>16</sub>	665 26 <sup>11</sup> / <sub>16</sub>	85 3 <sup>3</sup> / <sub>16</sub>	153°	97°	8 3/16"	Sx→Dx	CAT 2

Sliding companionway with shaped single wing.

The companionways are subject to quality control tests to comply with ISO 12216.2004 standards.

NOTE: Sx→Dx, Sx←Dx  
The sliding doors opening direction is always considered from the outside of the boat.

