

# Companionway 2537.05

model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	D (mm/ inch)	R (mm/ inch)	R1 (mm/ inch)	L (mm/ inch)	Le (mm/ inch)	H (mm/ inch)	He (mm/ inch)	S (mm/ inch)	α	glass (mm/inch)	opening	weather proof ISO 12216:2004
2537/05	650 25 <sup>19</sup> / <sub>16</sub>	1170 46 <sup>11</sup> / <sub>16</sub>	1230 48 <sup>3</sup> / <sub>16</sub>	1130 44 <sup>5</sup> / <sub>16</sub>	110 4 <sup>3</sup> / <sub>16</sub>	145 5 <sup>7</sup> / <sub>16</sub>	885 34 <sup>3</sup> / <sub>16</sub>	1575 62"	1140 44 <sup>9</sup> / <sub>16</sub>	1435 56 <sup>1</sup> / <sub>16</sub>	120 4 <sup>7</sup> / <sub>16</sub>	20°	17 7 <sup>1</sup> / <sub>16</sub> "	Sx→Dx	CAT 2

Sliding single-wing automatic companionway with inflatable gasket.

The companionways are subject to quality control tests to comply with ISO 12216.2004 standards. Weathertightness granted by the INFLATABLE GASKET. Pneumatic system composed of valves, hoses, pneumatic gasket, and compressor (if required).

NOTE: Sx→Dx, Sx←Dx  
The sliding doors opening direction is always considered from the outside of the boat.

