

# Companionway 2538

model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	D (mm/ inch)	R (mm/ inch)	R1 (mm/ inch)	L (mm/ inch)	Le (mm/ inch)	H (mm/ inch)	He (mm/ inch)	S (mm/ inch)	α	glass (mm/inch)	opening	weather proof ISO 12216:2023
2538/03	700 27 <sup>9</sup> / <sub>16</sub>	1175 46 <sup>1</sup> / <sub>4</sub>	1030 40 <sup>7</sup> / <sub>16</sub>	690 27 <sup>1</sup> / <sub>16</sub>	325 12 <sup>7</sup> / <sub>16</sub>	140 5 <sup>1</sup> / <sub>2</sub>	1850 72 <sup>3</sup> / <sub>16</sub>	1965 77 <sup>3</sup> / <sub>16</sub>	965 38"	1130 44 <sup>7</sup> / <sub>16</sub>	180 7 <sup>1</sup> / <sub>16</sub>	105°	11,5 2 <sup>1</sup> / <sub>16</sub> "	Sx→Dx	CAT 2
2538/13	700 27 <sup>9</sup> / <sub>16</sub>	1180 46 <sup>3</sup> / <sub>16</sub>	1190 46 <sup>9</sup> / <sub>16</sub>	655 25 <sup>9</sup> / <sub>16</sub>	325 12 <sup>7</sup> / <sub>16</sub>	350 13 <sup>7</sup> / <sub>16</sub>	1860 73 <sup>3</sup> / <sub>16</sub>	1965 77 <sup>3</sup> / <sub>16</sub>	940 36 <sup>9</sup> / <sub>16</sub>	1135 44 <sup>7</sup> / <sub>16</sub>	180 7 <sup>1</sup> / <sub>16</sub>	15°	13 1 <sup>1</sup> / <sub>16</sub> "	Sx→Dx	CAT 2

Sliding manual companionway composed of one fixed wing and a sliding one with inflatable gasket.

The companionways are subject to quality control tests to comply with ISO 12216.2023 standards. Weathertightness granted by the INFLATABLE GASKET.  
Pneumatic system composed of valves, hoses, pneumatic gasket, and compressor (if required).

NOTE: Sx→Dx, Sx←Dx  
The sliding doors opening direction is always considered from the outside of the boat.

