

# Companionway 2540.03



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	D (mm/ inch)	E (mm/ inch)	F (mm/ inch)	R (mm/ inch)	L (mm/ inch)	Le (mm/ inch)	H (mm/ inch)	He (mm/ inch)	S (mm/ inch)	Se (mm/ inch)	weather proof ISO 12216:2004
2540/03	1250 49 <sup>1</sup> / <sub>8</sub>	505 19 <sup>3</sup> / <sub>8</sub>	215 8 <sup>3</sup> / <sub>8</sub>	600 23 <sup>1</sup> / <sub>2</sub>	1325 52 <sup>1</sup> / <sub>8</sub>	750 29 <sup>1</sup> / <sub>2</sub>	40 1 <sup>3</sup> / <sub>8</sub>	1385 54 <sup>1</sup> / <sub>2</sub>	1410 55 <sup>1</sup> / <sub>2</sub>	555 21 <sup>3</sup> / <sub>8</sub>	790 31 <sup>1</sup> / <sub>8</sub>	105 4 <sup>1</sup> / <sub>8</sub>	140 5 <sup>3</sup> / <sub>8</sub>	CAT 2

Manual companionway with hinged double opening.  
The companionway is composed of a horizontal hatch and of a vertical one, both hinged.  
The vertical door has a 90° opening, the horizontal door opens upwards by means of gas springs.

The companionways are subject to quality control tests to comply with ISO 12216.2004 standards.

NOTE: Sx→Dx, Sx←Dx  
The sliding doors opening direction is always considered from the outside of the boat.

