

# Hatches pantograph system 2618.14



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	L (mm/ inch)	La (mm/ inch)	H (mm/ inch)	He (mm/ inch)	S (mm/ inch)	St (mm/ inch)	opening	weather proof ISO 12216:2023
2618/14	515 20 <sup>1</sup> / <sub>2</sub>	1100 43 <sup>3</sup> / <sub>10</sub>	460 18 <sup>1</sup> / <sub>10</sub>	640 25 <sup>3</sup> / <sub>10</sub>	660 26"	1375 54 <sup>1</sup> / <sub>2</sub>	1440 56 <sup>7</sup> / <sub>10</sub>	90 3 <sup>3</sup> / <sub>5</sub>	280 11"	Sx←Dx	CAT 2

Totally manual pantograph door (wing opening and lock/unlock).  
 Closing takes place by means of four manual locking pins.  
 The door is equipped with gas spring movement system to assist the operator during opening and closing.  
 Shaped wing made of fiberglass.

CERTIFIABLE BY RINA / BUREAU VERITAS / ABS / LLOYDS, please get in touch with our technical department to verify possible certifications.  
 The doors are subject to quality control tests to comply ISO 12216.2023 standards  
 NOTE: Sx→Dx, Sx←Dx  
 The sliding doors opening direction is always considered from the outside of the boat.

