

# Hatches pantograph system 2618.21



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	L (mm/ inch)	La (mm/ inch)	Lb (mm/ inch)	H (mm/ inch)	He (mm/ inch)	S (mm/ inch)	St (mm/ inch)	opening	weather proof ISO 12216:2004
2618/20	400 15 <sup>3</sup> / <sub>4</sub>	1145 45"	445 17 <sup>1</sup> / <sub>2</sub>	660 26 <sup>1</sup> / <sub>10</sub>	685 27"	695 27 <sup>1</sup> / <sub>2</sub>	1385 54 <sup>1</sup> / <sub>2</sub>	1395 55"	100 3 <sup>9</sup> / <sub>10</sub>	260 10 <sup>1</sup> / <sub>5</sub>	Sx↔Dx	CAT 2

Totally manual pantograph door (wing opening and lock/unlock).  
Closing takes place by means of four manual locking pins.  
The door is equipped with gas spring movement system to assist the operator during opening and closing.  
Shaped wing made of fiberglass.

CERTIFIABLE BY RINA / BUREAU VERITAS / ABS / LLOYDS, please get in touch with our technical department to verify possible certifications.  
The doors are subject to quality control tests to comply ISO 12216.2004 standards  
NOTE: Sx→Dx, Sx↔Dx  
The sliding doors opening direction is always considered from the outside of the boat.

