

# Hatches pantograph system 2619.03

model	A (mm/inch)	B (mm/inch)	C (mm/inch)	D (mm/inch)	L (mm/inch)	H (mm/inch)	S (mm/inch)	St (mm/inch)	opening	weather proof ISO 12216:2023
2619/03	670 26 <sup>3</sup> / <sub>8</sub>	1075 42 <sup>3</sup> / <sub>10</sub>	405 16"	350 13 <sup>7</sup> / <sub>10</sub>	780 30 <sup>7</sup> / <sub>10</sub>	1215 47 <sup>9</sup> / <sub>10</sub>	90 3 <sup>1</sup> / <sub>2</sub>	210 8 <sup>3</sup> / <sub>10</sub>	Sx←Dx	CAT 2



Totally manual pantograph door (wing opening and lock/unlock).  
Closing takes place by means of four manual locking pins.  
The door is equipped with gas spring movement system to assist the operator during opening and closing.  
Shaped wing made of aluminium.

CERTIFIABLE BY RINA / BUREAU VERITAS / ABS / LLOYDS, please get in touch with our technical department to verify possible certifications.  
The doors are subject to quality control tests to comply ISO 12216.2023 standards  
NOTE: Sx→Dx, Sx←Dx  
The sliding doors opening direction is always considered from the outside of the boat.

