

ELBOW CRANES model with fixed arm 3048/49

loading capacity 500 Kg to 800 Kg



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	Cmax (mm/ inch)	F (mm/ inch)	H (mm/ inch)	I (mm/ inch)	N (mm/ inch)	Cable lenght (mm/ inch)	Capacity standard (kg/ lbs)	Weight (kg/ lbs)
3048/26	1930 76"	2250 89"	2260 89"	2865 113"	2230 88"	575 22 ² / ₃ "	485 19"	245 9 ² / ₃ "	4500 177"	500/1100	405/890
3048/31	2330 92"	2650 104"	2800 110"	3510 138"	2575 101"	575 22 ² / ₃ "	485 19"	245 9 ² / ₃ "	7500 295"	500/1100	430/950
3049V24	2030 79 ⁹ / ₁₀ "	2640 103 ⁹ / ₁₀ "	2345 92 ¹ / ₃ "	2765 108 ⁴ / ₅ "	2835 111 ³ / ₅ "	720 28 ¹ / ₃ "	660 26"	290 11 ² / ₅ "	2500 98 ² / ₅ "	800/1760	630/1390

This crane can be certified for rescue boats and can be produced in compliance with S.O.L.A.S. requirements, upon request.
 ATTENTION! In case of certification request, dimensions and technical specifications may undergo significant variations.
 Please contact our Technical Department for information about the available certifications for the different crane models.
 Standard rotation 359°.
 Optional covers.

LEAD TIME TO BE CONFIRMED

These cranes can be certified by RINA SERVICE, BUREAU VERITAS, LLOYD REGISTER.

