

TELESCOPIC CRANES model 3085C

loading capacity 550 Kg to 1000 Kg



model	A (mm/ inch)	C (mm/ inch)	D (mm/ inch)	E (mm/ inch)	F (mm/ inch)	G (mm/ inch)	H (mm/ inch)	I (mm/ inch)	L (mm/ inch)	α	Capacity standard (kg/lbs)
3085C65	4227 166 ⁷ / ₈	6500 255 ⁹ / ₁₀	2272 89 ⁷ / ₈	1150 45 ³ / ₄	4200 165 ¹ / ₂	6707 264"	926 36 ¹ / ₂	850 33 ¹ / ₂	2180 85 ⁴ / ₅	60°	550/1210
3085C60	3950 155 ¹ / ₂	6000 236 ³ / ₅	2050 80 ⁷ / ₁₀	1025 40 ¹ / ₂	3945 155 ³ / ₁₀	6246 245 ⁹ / ₁₀	926 36 ¹ / ₂	850 33 ¹ / ₂	2040 80 ³ / ₁₀	60°	650/1430
3085C55	3700 145 ³ / ₅	5500 216 ¹ / ₂	1800 70 ⁹ / ₁₀	900 35 ³ / ₅	3742 147 ¹ / ₅	5828 229 ² / ₅	926 36 ¹ / ₂	850 33 ¹ / ₂	1935 76 ¹ / ₅	60°	750/1650
3085C50	3500 138"	5000 197"	1500 59"	750 30"	3655 144"	4960 195"	926 36 ¹ / ₂	850 33 ¹ / ₂	1900 75"	60°	870/1920
3085C45	3200 126"	4500 177 ¹ / ₅	1300 51 ¹ / ₅	650 25 ³ / ₅	3290 129 ¹ / ₂	4947 194 ³ / ₄	926 36 ¹ / ₂	850 33 ¹ / ₂	1675 66"	60°	1000/2200

Group of cranes certified with Bureau Veritas type approval.

Swivelling flybridge crane with 359° standard rotation and 5m maximum reach, made of painted AISI 316L stainless steel with optional GRP cover.

This crane has a maximum loading capacity of 1000kg and a maximum cable length of 8m. Suitable for rescue boats.

LEAD TIME TO BE CONFIRMED

