

TENDER LIFT WITH ANGULAR FIXING SYSTEM 5221/24

loading capacity 300 to 1000 Kg



model	A (mm/ inch)	A1 (mm/ inch)	B (mm/ inch)	C (mm/ inch)	F (mm/ inch)	f (mm/ inch)	G (mm/ inch)	L (mm/ inch)	M (mm/ inch)	α	β	R (mm/ inch)	S (mm/ inch)	capacity standard (kg/lbs)
5221/95.01	265 10" 1/2	555 21" 4/5	940 37"	550 21" 2/3	1010 40"	730 29"	380 15"	205 8"	235 9" 1/4	16,5°	106,5°	200 7" 4/5	215 8" 1/2	300/660
5221/95.03	275 20" 4/5	605 23" 4/5	955 37" 3/5	750 29" 3/5	1080 42" 3/5	855 33" 3/5	375 14" 3/5	160 6" 1/5	190 7" 3/5	17°	114°	200 7" 4/5	225 8" 1/2	300/660
5221/80.01	520 20" 3/5	590 23" 1/5	775 30" 3/5	550 21" 2/3	990 39"	720 28" 3/5	350 13" 4/5	150 6"	180 7"	14°	109°	200 7" 4/5	225 8" 1/2	600/1320
5224/12.01	540 21" 1/4	775 30" 1/2	1160 45" 3/5	1000 39" 3/5	1020 40"	885 34" 4/5	530 20" 4/5	210 8" 1/4	250 9" 4/5	2°	93°	280 11"	160 6" 1/3	1000/2200

To be installed on bulwarks with extended fixed platform portion.

Note: The declared lifting capacity is assured if the load is positioned in the middle of measure C. The loading capacity includes the total platform weight (at shipyard's care), the full loaded tender or the jet ski.

Tender lift standard version is electro-polished only.

LEAD TIME TO BE CONFIRMED

