

# TENDER LIFT 5231.80

loading capacity 500 Kg



| model      | A<br>(mm/inch)                        | B<br>(mm/inch)                         | C<br>(mm/inch)                        | F<br>(mm/inch) | f<br>(mm/inch)                         | L<br>(mm/inch)                        | M<br>(mm/inch)                         | R<br>(mm/inch)                        | S<br>(mm/inch)                       | capacity<br>standard<br>(kg/lbs) |
|------------|---------------------------------------|----------------------------------------|---------------------------------------|----------------|----------------------------------------|---------------------------------------|----------------------------------------|---------------------------------------|--------------------------------------|----------------------------------|
| 5231/80.01 | 392<br>15 <sup>7</sup> / <sub>8</sub> | 780<br>30 <sup>7</sup> / <sub>16</sub> | 650<br>25 <sup>3</sup> / <sub>8</sub> | 965<br>38"     | 1215<br>47 <sup>1</sup> / <sub>8</sub> | 385<br>15 <sup>1</sup> / <sub>8</sub> | 4.5<br>1 <sup>1</sup> / <sub>8</sub> " | 285<br>11 <sup>1</sup> / <sub>8</sub> | 140<br>5 <sup>1</sup> / <sub>2</sub> | 500/1100                         |

Tender lift with prearrangement for platform frame fastening. Prearrangements are present on the arms and on platform support brackets.

Note: The declared lifting capacity is assured if the load is positioned in the middle of measure C. The loading capacity includes the total platform weight (at shipyard's care), the full loaded tender or the jet ski. Tender lift standard version is electro-polished only.

