

loading capacity 300 to 500 Kg



model	A (mm/inch)	B (mm/inch)	C (mm/inch)	D (mm/inch)	E (mm/inch)	F (mm/inch)	dynamic load (kg/lbs)	static load (kg/lbs)
5250/90	860 33" 3⁄5	900 35" 2⁄5	595 23" 3⁄5	220 8" 3⁄5	196 7" 3⁄4	152 6"	300/660	300/660
5255/90	860 33" 3⁄5	900 35" 2⁄5	805 31" 3⁄4	170 6" 7⁄10	330 13"	190 7" 1⁄2	500/1100	650/1400
POSSIBLE CUSTOMIZATION OF DIMENSIONS								

Transom system with UP&DOWN vertical movement and extendable/retractable steps. When the platform is lowered, the steps offer to the user a comfortable and safe access to water and easy on boarding from the sea just as if he were in his own swimming pool.

The possibility to rise the S.A.F.E. system and lift the steps, makes it easy, safe, and comfortable to get on board from the dock.
At the same time, this allows the outboard motors rise and the positioning of propellers out of the water during the mooring.

S.A.F.E. system 5250/55 can be fitted on any type of boat, both as refit and first installation, allowing you to enjoy an increased walkway surface on your boat.

Customizations can be made according to your boat design (2 to 5 steps and platform support).

