

# EVO TENDER LIFT 5280/81/82

## loading capacity 300 Kg to 850 Kg



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	D (mm/ inch)	E (mm/ inch)	I (mm/ inch)	S (mm/ inch)	X (mm/ inch)	Y (mm/ inch)	dynamic load (kg/lbs)	static load (kg/lbs)
5280/11.01	380 15"	1160 45" 1/2	310 12" 1/5	1320 52"	2760 108" 3/5	1895 74" 3/5	272 10" 3/4	480 19"	680 26" 4/5	300/660	400/880
5281/11	410 16" 1/10	1160 45" 1/2	295 11" 3/5	1320 52"	2200 86" 3/5	1895 74" 3/5	322 12" 7/10	420 16" 1/2	740 29" 1/10	600/1320	750/1650
5282/13	680 36" 3/4	1290 50" 3/4	935 36" 4/5	2035 80" 1/10	2590 102"	2255 88" 3/4	166 6" 1/2	400 15" 3/4	890 35"	850/1875	1060/2330

While S.A.F.E. systems are conceived for outboard motorboats, EVO TENDER LIFT has been specifically created for inboard motorboats.

Transom system with UP&DOWN pantograph movement and extendable/retractable steps. When the platform is lowered, the steps offer to the user a comfortable and safe access to water and easy on boarding from the sea just as if he were in his own swimming pool.

The possibility to rise the EVO TENDER LIFT system and lift the steps, makes it easy, safe, and comfortable to get on board from the dock.

EVO TENDER LIFT can be fitted on any type of boat, both as refit and first installation, allowing you to enjoy an increased walkway surface on your boat.

During navigation, the product must be kept in high position.

Customizations can be made according to your boat design.

