

SLIDER LIFT model 5425

loading capacity 800 Kg



model	A (mm/ inch)	A1 (mm/ inch)	B (mm/ inch)	C (mm/ inch)	f (mm/ inch)	L (mm/ inch)	L1 (mm/ inch)	M (mm/ inch)	α	R (mm/ inch)	R1 (mm/ inch)	S (mm/ inch)	T (mm/ inch)	capacity standard (kg/lbs)
5425/13	1127 44 ³ / ₈	1145 45"	1300 51 ¹ / ₈	1242 48 ⁹ / ₁₀	-191 7 ¹ / ₂	621 24 ³ / ₈	1371 54"	148 5 ⁷ / ₈	30°	220 8 ³ / ₈	911 35 ³ / ₈	245 9 ³ / ₈	331 13"	800/1763

POSSIBLE CUSTOMIZATION OF DIMENSIONS

Slider lift system to be installed on transom area, ideal for yachts featuring inclined sterns and beach platform resting on the fixed part.

It is made of AISI 316L stainless steel, electropolished, and mirror polished visible parts.

This system allows the platform to slide horizontally, come out of the bulwark and approach the dock to ease the access to the boat.

It also allows the platform to go under the water line to enable hauling and launching of tenders and jet skis.

PATENTED SYSTEM

