

MULTIFUNCTION GANGWAYS 3261

extension 2720 mm to 4050 mm, H box: 230 mm



| model | A (mm/ inch) | B (mm/ inch) | C (mm/ inch) | D (mm/ inch) | E (mm/ inch) | G (mm/ inch) | L (mm/ inch) | H (mm/ inch) | α | β | n° steps |
|-----------|---|---|---|--|--|-----------------|-----------------|-----------------|----------|---------|-------------|
| - 3261/28 | 2720 107" | 3420 134 ² / ₃ " | 170 6 ² / ₃ " | 1544 60 ⁴ / ₅ " | 1544 60 ⁴ / ₅ " | 440 17" | 710 28" | 230 9" | 40° | 40° | 9 |
| - 3261/41 | 4050 159 ³ / ₅ " | 4750 187" | 900 34 ³ / ₅ " | 1930 76" | 1930 76" | 440 17" | 710 28" | 230 9" | 40° | 40° | 11 |

Optional box: weathertight, watertight and certificated watertight.

This gangway allows passengers boarding only, up to 150 Kg / 330 lbs (one person at a time).
No tender lifting allowed.

NEVER USE THE GANGWAY AS SPRINGBOARD. DIVING COULD CAUSE STRONG STRAINS THAT MIGHT DAMAGE THE GANGWAY AND ITS FASTENING ELEMENTS.

OPTIONAL LANDING AND XXL BOX

- LEAD TIME TO BE CONFIRMED

