

MULTIFUNCTION GANGWAYS 3622SC

extension 1800 mm to 2450 mm, H box: 195 mm to 205 mm



model	A (mm/ inch)	B (mm/ inch)	C (mm/ inch)	D (mm/ inch)	E (mm/ inch)	G (mm/ inch)	L (mm/ inch)	H (mm/ inch)	α	β	n° steps
- 3622SC/18	1800 70 ⁹ / ₁₀	2600 102 ² / ₃	330 13"	962 37 ⁹ / ₁₀	962 37 ⁹ / ₁₀	426 16 ⁴ / ₅	590 23 ¹ / ₅	195 7 ⁷ / ₁₀	40°	40°	6
3622SC/21	2100 82 ⁷ / ₁₀	2900 114 ¹ / ₅	330 13"	1155 45 ¹ / ₂	1155 45 ¹ / ₂	426 16 ⁴ / ₅	590 23 ¹ / ₅	195 7 ⁷ / ₁₀	40°	40°	7
- 3622SC/24	2390 94"	3200 126"	330 13"	1348 53"	1348 53"	426 16 ⁴ / ₅	590 23 ¹ / ₅	195 7 ⁷ / ₁₀	40°	40°	8
3622SC/26	2450 96 ¹ / ₂	3380 133"	355 14"	1220 48"	1700 66 ⁹ / ₁	525 20 ⁷ / ₁₀	710 28"	205 8"	36°	55°	8

Optional box: weathertight, watertight and certificated watertight.

This gangway allows passengers boarding only, up to 150 Kg / 330 lbs (one person at a time). No tender lifting allowed.

NEVER USE THE GANGWAY AS SPRINGBOARD. DIVING COULD CAUSE STRONG STRAINS THAT MIGHT DAMAGE THE GANGWAY AND ITS FASTENING ELEMENTS.

OPTIONAL LANDING AND XXL BOX

- LEAD TIME TO BE CONFIRMED

