

TENDER LIFT FOR CATAMARANS 5240

loading capacity 600 Kg to 1400 Kg

model	A (mm/ inch)	A1 (mm/ inch)	B (mm/ inch)	C (mm/ inch)	C1 (mm/ inch)	F (mm/ inch)	f (mm/ inch)	f1 (mm/ inch)	L (mm/ inch)	M (mm/ inch)	α	R (mm/ inch)	R1 (mm/ inch)	S (mm/ inch)	Material	capacity standard (kg/lbs)	weight (kg/lbs)
5240/17	467 18 ³ / ₅	1025 40 ¹ / ₃	1695 66 ³ / ₄	1580 62 ¹ / ₅	1665 65 ¹ / ₂	470 18 ¹ / ₂	685 27"	595 23 ³ / ₅	-213 8 ² / ₅	385 15 ¹ / ₁₀	0°	445 17 ¹ / ₂	245 9 ³ / ₅	230 9"	AISI 316L	600/1320	525/1155
5240/20	467 18 ³ / ₅	1025 40 ¹ / ₃	2005 78 ⁹ / ₁₀	1580 62 ¹ / ₅	1665 65 ¹ / ₂	720 28 ¹ / ₃	1084 42 ³ / ₅	994 39 ¹ / ₁₀	-362 -14 ¹ / ₄	385 15 ¹ / ₁₀	0°	445 17 ¹ / ₂	245 9 ³ / ₅	230 9"	AISI 316L	700/1540	555/1220
5240/27	467 18 ³ / ₅	1025 40 ¹ / ₃	2620 103 ¹ / ₁₀	1580 62 ¹ / ₅	--	815 32"	1320 52"	--	-415 -16 ¹ / ₃	650 16 ² / ₃	2°	--	250 9 ³ / ₅	230 9"	AISI 316L	1400/3085	800/1765



Lifting mechanism for hydraulic stern platforms that allow and ease dinghies, tenders and jet skis hauling.
 Supplied in two arms combinations, they are fully made of steel AISI 316L.
 Compared to our traditional Tender Lift, this new type is particularly suitable for catamarans, as it better fits to boat transom, thanks to its reduced height, however granting a high platform stroke.
 Customisable dimensions and loading capacities to meet your requirements.

— LEAD TIME TO BE CONFIRMED

